

Quantum Physics

Derivation of sensitivity of a Geiger mode APDs detector from a given efficiency for QKD experiments

Kiyotaka Hammura, David Williams

(Submitted on 5 Jan 2009)

The detection sensitivity (DS) of the commercial single-photon-receiver based on InGaAs gate-mode avalanche photodiode is estimated. Instalment of a digital-blanking-system (DBS) to reduce dark current makes the difference between DS, which is an efficiency of the detector during its open-gate/active state, and the total/overall detection efficiency (DE). By numerical simulations, it is found that the average number of light-pulses, blanked by DBS, following a registered pulse is 0.333. DS is estimated at 0.216, which can be used for estimating DE for an arbitrary photon arriving rate and a gating frequency of the receiver.

Comments: 7 pages, 2 figures, 1 table

Subjects: **Quantum Physics (quant-ph)**DOI: [10.1088/1464-4258/11/5/054003](https://doi.org/10.1088/1464-4258/11/5/054003)Cite as: [arXiv:0901.0525v1](https://arxiv.org/abs/0901.0525v1) [quant-ph]

Submission history

From: Kiyotaka Hammura [[view email](#)]

[v1] Mon, 5 Jan 2009 17:14:00 GMT (446kb)

[Which authors of this paper are endorsers?](#)

Download:

- [PDF](#)
- [PostScript](#)
- [Other formats](#)

Current browse context:

quant-ph

[< prev](#) | [next >](#)[new](#) | [recent](#) | [0901](#)

References & Citations

- [SLAC-SPIRES HEP](#)
([refers to](#) | [cited by](#))
- [CiteBase](#)

Bookmark (what is this?)

 [CiteULike logo](#) [Connotea logo](#) [BibSonomy logo](#) [Mendeley logo](#) [Facebook logo](#) [del.icio.us logo](#) [Digg logo](#) [Reddit logo](#)