



发光学报 2013, 34(6) 807-810 ISSN: 1000-7032 CN: 22-1116/O4

发光学应用及交叉前沿

用于农田土壤监测的高光谱成像仪

金辉^{1,2}, 姜会林¹, 郑玉权², 张晓辉², 崔继承²

1. 长春理工大学, 吉林 长春 130022;

2. 中国科学院 长春光学精密机械与物理研究所, 吉林 长春 130033

PDF 下载

引用本文

摘要：土壤光谱分析技术具有分析速度快、成本低、无危险、无破坏、可同时反演多种成分等特点,基于高光谱成像技术可以快速获取土壤性质及其空间分布特征。本文针对农田土壤监测的需求,设计了一种无人机载高光谱成像仪,选择Offner凸光栅光谱成像系统实现了无谱线弯曲和无色畸变的设计结果。400~1 000 nm波长范围内的衍射效率为15%~30%,对地成像效果清晰,在3 km飞行高度可以获得覆盖宽度为0.6 km、地面分辨率为0.6 m的地物目标高光谱图像,可提供0.4~1.0 μm波长范围内120个谱段的高光谱图像,光谱数据准确、稳定。结果表明,该高光谱成像仪满足设计要求且可以快速获得高精度成像光谱信息,适用于对农田土壤的监测。

关键词：高光谱成像仪 农田土壤 监测

本刊中的类似文章

1. 多层AlGaAs的时间分辨归一化反射率及各向异性反射率谱在线监测及分析[J]. 2012,(5): 509-513
2. 太阳辐射的在轨监测和定标[J]. 2010,31(5): 676-681
3. 用于农田土壤监测的高光谱成像仪[J]. .(): 0-0

Hyperspectral Imager for Farmland Soil Monitoring

JIN Hui^{1,2}, JIANG Hui-lin¹, ZHENG Yu-quan², ZHANG Xiao-hui², CUI Ji-cheng²

1. Changchun University of Science and Technology, Changchun 130022, China;

2. Changchun Institute of Optics, Fine Mechanics and Physics, Chinese Academy of Sciences, Changchun 130033, China

Abstract: Soil spectral analysis technology has features of fast analysis speed, low cost, no risk, no damage, and it can inverse a variety of ingredients at the same time. Based on hyper-spectral imaging technology, we can quickly obtain soil properties and its spatial distribution characteristics. In this paper, we design a UAV hyper-spectral imager based on the demand of farmland soil monitoring. The Offner convex grating spectral imaging system was selected to achieve non-spectral line bending and colorless distortion design results. The diffraction efficiency is 15%~30% in the range of 400~1 000 nm wavelength. The ground imaging results are clear, it can obtain hyper-spectral images of ground target of covering a width of 0.6 km and ground resolution of 0.6 m at 3 km altitude. It provides 120 spectral bands of hyper-spectral images at the wavelength range of 0.4~1.0 μm. The spectral data are accurate and stable. The results show that this hyper-spectral imager meets the design requirements and can quickly obtain the high-precision imaging spectra of the agricultural soils, thus achieving the monitoring of farmland soil.

Keywords: hyperspectral imager farmland soil monitor

收稿日期 2013-03-02 修回日期 2012-04-13 网络版发布日期

基金项目:

国家“863”高技术发展研究计划(2008AA121803)资助项目

通讯作者: 郑玉权

作者简介: 金辉(1979-),女,吉林长春人,主要从事航空航天光机系统设计、检测方面的研究。E-mail:jjhh0118@hotmail.com

作者Email: derek_zheng001@hotmail.com

参考文献:

- [1] O'neal A M. The effect of moisture on the color of certain Iowa soils[J]. *American Soil Survey Association Bulletin*,1927(B8):158-174.
- [2] Zheng Y Q, Yu B X. Overview of spectrum-dividing technologies in imaging spectrometers[J]. *J. Remote Sensing (遥感学报)*,2002, 6(1):75-80 (in Chinese).
- [3] Galvo L S, Formaggio A R, Couto E G, *et al.* Relationships between the mineralogical and chemical composition of tropical soils and topography from hyperspectral remote sensing data[J]. *ISPRS J. Photogrammetry and Remote Sensing*
- [4] Selige T, B hner J, Schmidhalter U. High resolution topsoil mapping using hyperspectral image and field data in multivariate regression modeling procedures[J]. *Geoderma*
- [5] Gomez C, Rossel R A V, McBratney A B. Soil organic carbon prediction by hyperspectral remote sensing and field Vis-NIR spectroscopy: An Australian case study[J]. *Geoderma*
- [6] Qi X D, Han P P, Pan M Z, *et al.* Spectral calibration of imaging spectrometer with convex grating[J]. *Opt. Precision Eng. (光学 精密工程)*
- [7] Zheng Y Q. Precise spectral calibration for hyperspectral imager[J]. *Opt. Precision Eng. (光学 精密工程)*,2010, 18(11):2347-2354 (in Chinese).
- [8] Zheng Y Q. Design of compact Offner spectral imaging system[J]. *Opt. Precision Eng. (光学 精密工程)*,2005, 13

