

Journal of Environmental Hydrology

ISSN 1058-3912

Electronic Journal of the International Association for Environmental Hydrology

JEH Volume 12 (2004), Paper 4, March 2004

Posted March 14, 2004

DEM-RS-GIS BASED STORM RUNOFF HYDROGRAPH ESTIMATION FOR THE HEART RIVER SUB-BASIN,
MISSOURI RIVER BASIN

Assefa M. Melesse

Earth Systems Science Institute, University of North Dakota, Grand Forks, North Dakota, USA

ABSTRACT

Accurate representation of the physical and biological features of the landscape within the watershed is required as the extent and type of watershed cover affects the movement of water in the hydrologic cycle. Remote sensing (RS), such as satellite imagery from Landsat and other satellites, provides land-cover and surface microclimate information with high temporal and spatial accuracy. The use of these data to understand hydrologic processes depends on how accurately they are interpreted and mapped. A study conducted at the Heart River sub-basin in the Missouri River basin, located on southwestern North Dakota, utilizes Landsat Enhanced Thematic Mapper Plus imagery and geographic information system (GIS) tools to derive landcover for the summer of 2002. Land surface temperature and Normalized Difference Vegetation Index (NDVI) from the Landsat image was used to better map the land-cover and estimate runoff response. The corresponding infiltration excess runoff response of the study area was estimated using the United States Department of Agriculture, Natural Resources Conservation Service Curve Number (USDA-NRCS-CN) method. A Digital Elevation Model (DEM)-RS-GIS routing technique based on a 1-D kinematic wave approximation was developed to predict stream response to runoff events based on the travel time from each grid cell to the watershed outlet. Simulated and observed runoff volume and hydrographs were compared for three storm events. The NRCS-CN method with the DEM-RS-GIS routing technique predicts the observed runoff volume with mean error and residual standard deviation of (-38% and 5 mm), peak flow (-15% and 2.38 m³/sec), and time to peak flow (17% and, 1.26 day), respectively.

Reference: Melesse, A. M. ; DEM-RS-GIS based Storm Runoff Hydrograph Estimation for the Heart River Sub-basin, Missouri River Basin, Journal of Environmental Hydrology, Vol. 12, Paper 4, March 2004.

CONTACT:

Assefa M. Melesse

Assistant Professor

Earth Systems Science Institute

University of North Dakota

Grand Forks, ND 58202

USA

E-mail: assefa@aero.und.edu

[Return to HydroWeb Homepage](#)