

未定

一种凸轮材料的表面强化及摩擦学特性研究

李月英,刘勇兵,陈华

吉林大学材料学院

收稿日期 2006-9-22 修回日期 网络版发布日期 2006-12-6 接受日期

摘要 本论文研究了汽车用铁基烧结凸轮材料在三种表面处理状态下（烧结态、激光表面淬火和高频感应淬火）的显微组织、显微硬度及其摩擦学特性。研究结果表明：经两种表面淬火后，材料的表面得到一均匀的硬化层，其组织为细针状的马氏体组织，其耐磨性和摩擦系数得到了显著的改善。激光淬火凸轮材料的表面摩擦学特性略优于高频淬火凸轮材料。在本试验参数范围内，随着试验载荷的提高，激光淬火铁基烧结凸轮材料的磨损机制将发生转变，由轻微氧化磨损和磨粒磨损机制转化为严重氧化磨损、磨粒磨损和剥层磨损机制。

关键词 [粉末冶金](#) [凸轮材料](#) [表面强化](#) [摩擦学特性](#)

分类号

### Surface hardened and tribological properties of a cam materials

吉林大学材料学院

**Abstract** Microstructure, microhardness and tribological properties of ferrous P/M cam materials for automobile applications are investigated under three conditions (as-sintered, high-frequency induction quenched and wide-band laser surface quenched). The experimental results indicated that a hardened layer was obtained on the surface of the materials after two surface hardened. Microstructure of the hardened layer was fine spiculate martensite which can help to improve the wear and friction properties of the materials. The tribological properties of laser surface quenched cam materials were slightly better to high-frequency induction quenched cam materials. With the increasing of test loads the wear mechanism of laser quenched cam materials would change from mild oxidation wear and abrasive to severe oxidation wear, abrasive wear and delamination wear.

**Key words** [P/M](#) [cam materials](#) [surface quenched](#) [Tribological properties](#)

DOI:

通讯作者 李月英 [yueying@jlu.edu.cn](mailto:yueying@jlu.edu.cn)

扩展功能	
本文信息	
▶ <a href="#">Supporting info</a>	
▶ <a href="#">PDF(0KB)</a>	
▶ <a href="#">HTML全文(0KB)</a>	
▶ <a href="#">参考文献</a>	
服务与反馈	
▶ <a href="#">把本文推荐给朋友</a>	
▶ <a href="#">复制索引</a>	
▶ <a href="#">文章反馈</a>	
▶ <a href="#">浏览反馈信息</a>	
相关信息	
▶ <a href="#">本刊中 包含“粉末冶金”的相关文章</a>	
▶ 本文作者相关文章	
· <a href="#">李月英</a>	
· <a href="#">刘勇兵</a>	
· <a href="#">陈华</a>	