

Β

Agricultural Journals

Research in AGRICULTURAL ENGENEERING

home page about us contact

	US
able of Contents	
N PRESS	
RAE 2013	
RAE 2012	
RAE 2011	
RAE 2010	
RAE 2009	
RAE 2008	
RAE 2007	
RAE 2006	
RAE 2005	
RAE 2004	
RAE 2003	
RAE Home	
Editorial	
oard	

For Authors

- Authors
 Declaration
- Instruction to Authors
- Guide for Authors
- Copyright
 Statement
- Submission

For Reviewers

- Guide for Reviewers
- Reviewers
 Login

Subscription

Res. Agr. Eng.

Koszel M.: Influence of fan flat nozzles wear degree on drop tracks size Res. Agr. Eng., 55 (2009): 39-44

The subject of the analysis was the influence of working parameters (working pressure and working speed) on the drop tracks size and changes in the flow rate level from flat fan nozzles. New nozzles were tested. It was found that the increase in the flow rate depends on the nozzles size and their working time, and that the increase in the drop track size is caused by the nozzles wear. An excessively low working pressure or working speed causes drops merging. This phenomenon is especially dangerous when using nozzles with a considerable degree of wear for agricultural spray since it poses ecological threat to the environment.

Keywords:

spray; drop tracks size; nozzles wear; flow rate

[fulltext]

© 2011 Czech Academy of Agricultural Sciences