

本期目录 | 下期目录 | 过刊浏览 | 高级检索

[打印本页] [关闭]

激光与光电子技术应用

铝材管道管壁厚度对激光超声信号影响的探究

王贵鑫, 严刚, 关建飞

南京邮电大学 光电工程学院, 南京 210023

摘要: 为了探究管壁厚度对超声信号的产生与探测的影响, 采用有限元法建立了理想化的管道模型, 分别探究均匀管壁厚度变化和激发源处、接收端处及传播路径上等畸变管壁厚度的变化对超声信号产生的影响。结果表明, 当接收端处管壁厚度较薄时, 无法探测到可分辨的瑞利波信号; 传播路径上管壁厚度变小到一定程度后, 高频成分会出现明显的衰减, 但随着厚度的增大又会在一定程度内恢复。这一结果对激光超声在柱状、管状材料的无损检测中的进一步应用提供了有益的补充。

关键词: 激光技术 激光超声 有限元法 无损检测

Effect of wall thickness of aluminum pipes on laser-induced ultrasonic waves

WANG Guixin, YAN Gang, GUAN Jianfei

College of Electronic Engineering, Nanjing University of Posts and Telecommunications, Nanjing 210023, China

Abstract: In order to explore effect of wall thickness on the generation and detection of ultrasound signal, several idealized eccentric pipe models were established based on the finite element method. Effect of different uniform wall-thickness and thickness change at the excitation source, detection point and the propagation path on ultrasonic signal was analyzed. The simulation results show that: when the wall is thinner, the Rayleigh waves cannot be detected; the wall thickness on the propagation path becomes small to some extent, the filtering effect will be so obvious that the high-frequency component is filtered out, but will resume within a certain extent in the pipes with thicker wall. This work will provide a useful guidance for the further application of laser ultrasonic in cylinder nondestructive testing field.

Keywords: laser technique laser ultrasonic finite element method nondestructive testing

收稿日期 2013-03-18 修回日期 2013-06-05 网络版发布日期 2014-01-06

DOI: 10.7510/jgjs.issn.1001-3806.2014.02.024

基金项目:

通讯作者: 严刚

作者简介: 王贵鑫 (1986-), 男, 硕士研究生, 主要从事激光超声的数值模拟研究。

作者Email: yang@njupt.edu.cn

参考文献:

- [1] WU X, QIAN M, CANTRELL J H. Dispersive properties of cylindrical Rayleigh waves [J]. Applied Physics Letters, 2003, 83(19): 4053-4055.
- [2] HU W, QIAN M, CANTRELL J H. Thermoelastic generation of cylindrical rayleigh waves and whispering gallery modes by pulsed-laser excitation [J]. Applied Physics Letters, 2004, 85(18): 4031-4033.
- [3] PAN Y, ROSSIGNOL C, AUDOIN B. Acoustic waves generated by a laser line pulse in a transversely isotropic cylinder [J]. Applied Physics Letters, 2003, 82(24): 4379-4381.
- [4] FRANK S, BERND K, ALEXANDER P. Time domain modeling of axisymmetric wave propagation in isotropic elastic media with CEFIT-cylindrical elastodynamic finite integration technique [J]. Journal of Computational Acoustics, 2001, 9(3): 1127-1146.
- [5] DONG L M, LI J, NI Ch, et al. Crack detection of engine blade based on laser-heating assisted surface acoustic waves generated by scanning laser[J]. Chinese Journal of Lasers, 2011, 38(11): 84-88(in

扩展功能

本文信息

► Supporting info

► PDF(1479KB)

► [HTML全文]

► 参考文献[PDF]

► 参考文献

服务与反馈

► 把本文推荐给朋友

► 加入我的书架

► 加入引用管理器

► 引用本文

► Email Alert

► 文章反馈

► 浏览反馈信息

本文关键词相关文章

► 激光技术

► 激光超声

► 有限元法

► 无损检测

本文作者相关文章

► 王贵鑫

► 严刚

► 关建飞

PubMed

► Article by WANG Guixin

► Article by YAN Gang

► Article by GUAN Jianfei

Chinese).

- [6] FENG W, YANG D X, LIAO W, et al. Numerical simulation of laser induced ultrasonic in a diamond anvil cell by finite element method[J]. Chinese Journal of Lasers, 2011, 38(8): 89-94(in Chinese).
- [7] LIU J Sh, XU Zh H, GU G Q. Numerical study on improvement of signal-to-noise ratio of surface acoustic waves based on laser array[J]. Laser Technology, 2011, 35(3): 403-406(in Chinese).
- [8] CAO D D, WANG K Sh, YANG Y Y. Fintite element simulation of temperature field of thin tubes irradiated by ring lasers[J]. Laser Technology, 2010, 34(6): 753-756(in Chinese).
- [9] CLORENNEC D, ROYER D, CATEELINE S. Saw propagating on cylindrical parts using laser-ultrasonics: application to crack deflection [J]. IEEE Ultrasonics Symposium, 2002, 1(8/11): 207-210.
- [10] ZHAO Y. Theoretical and experimental study of the laser-induced ultrasonic waves at fluid-solid interface and curved surface[D]. Nanjing: Nanjing University of Science and Technology, 2007: 5-19 (in Chinese).
- [11] HE Y J, ZHU R H, SHEN Zh H, et al. Simulation of laser-induced temperature fields and rayleigh waves in thick Al pipe[J]. Journal of Nanjing University of Science and Technology, 2005, 29(4): 468-471(in Chinese).

本刊中的类似文章

1. 陈爽, 冯莹, 王玲. 基于GLM的多模光纤放大器模式控制研究[J]. 激光技术, 2010, 34(1): 128-131
2. 于益, 王卫民, 鲁燕华, 谢刚, 彭跃峰. 二极管激光光谱合束技术实验研究[J]. 激光技术, 2010, 34(1): 138-140
3. 张芳沛, 楼祺洪, 李红霞, 韩文杰, 邢宇华, 董景星, 沈严, 薛海中. 1064nm激光诱导等离子体开关控制355nm脉宽可调输出[J]. 激光技术, 2010, 34(1): 17-19, 40
4. 卢彦兆, 王新兵, 董旬, 张学玲. 双波长可调谐TEA CO₂激光器的脉冲输出特性[J]. 激光技术, 2010, 34(1): 88-90, 94
5. 何建平, 周智, 吴源华, 欧进萍. 光纤布里渊与布喇格光栅共线技术的温度互补偿[J]. 激光技术, 2010, 34(1): 13-16
6. 余阳春, 王春明, 余圣甫. 5A06铝合金的激光填丝焊接头组织与性能[J]. 激光技术, 2010, 34(1): 34-36, 52
7. 秦海永, 张永康, 尤建. 高能激光辐照诱导声波频率特性的实验研究 [J]. 激光技术, 0, (): 105-105
8. 储晓猛, 顾佩兰, 杨建新. 高密度聚乙烯塑料激光焊接工艺参数试验研究[J]. 激光技术, 2010, 34(1): 116-119
9. 姜银方, 应才苏, 刘赤荣, 石朝阳, 周桂生. 激光功率密度对板料激光冲击成形性能的影响[J]. 激光技术, 2010, 34(1): 95-98
10. 柳娟, 唐霞辉, 彭浩, 秦应雄, 邓前松. 高效率3工位激光焊接系统的控制优化[J]. 激光技术, 2010, 34(1): 56-59

Copyright by 激光技术