

电子与信息学报

JOURNAL OF ELECTRONICS & INFORMATION TECHNOLOGY

首页 | 期刊介绍 | 编 委 会 | 投稿指南 | 期刊订阅 | 联系我们 | 留言板 | English

电子与信息学报 » 2011, Vol. 33 » Issue (5):1082-1087 DOI: 10.3724/SP.J.1146.2010.01067

仑文

最新目录 | 下期目录 | 过刊浏览 | 高级检索

<< Previous Articles | Next Articles >>

一种基于频域子带合成的多发多收高分辨率SAR成像算法

邓云凯① 陈倩*① 祁海明① 郑慧芳① 刘亚东②*

①(中国科学院电子学研究所 北京 100190) ②(中国空间技术研究院总体部 北京 100094)

A High-resolution I maging Algorithm for MIMO SAR Based on the Sub-band Synthesis in Frequency Domain

Deng Yun-kai $^{\scriptsize 0}$ Chen Qian $^{\scriptsize 0}$ Qi Hai-ming $^{\scriptsize 0}$ Zheng Hui-fang $^{\scriptsize 0}$ Liu Ya-dong $^{\scriptsize 2}$ *

①(Institute of Electronics, Chinese Academy of Sciences, Beijing 100190, China) ②(China Academy of Space Technology, Beijing 100094, China)

摘要

参考文献

相关文章

Download: PDF (643KB) HTML 1KB Export: BibTeX or EndNote (RIS)

Supporting Info

摘要 针对传统单通道SAR系统无法同时实现方位向高分辨率和大测绘带宽的不足,该文研究了一种基于多载频LFM波形的方位多孔径MIMO SAR系统,建立了相应的几何模型,详细推导了其回波表达式,并提出了一种基于频域子带合成的MIMO SAR高分辨率成像算法。该算法将方位向多普勒解模糊,改进的距离向频域子带合成和CS成像算法相结合,能够同时实现2维高分辨率和大测绘带宽,且提出的频域子带合成法较传统时域和频域合成法更高效实用。理论分析和计算机仿真结果验证了其有效性。

关键词: 合成孔径雷达 多发多收 高分辨率宽测绘带 多普勒模糊 频域子带合成

Abstract: Considering the contradiction between the azimuth resolution and the swath width for the traditional SAR, a MIMO SAR system with multiple-carrier-frequency LFM waveform is researched. The corresponding geometrical?model is built, and the expressions of the echo signals are derived in detail. A novel imaging algorithm based on the sub-band synthetic technology in frequency domain is proposed. This algorithm which integrates the removing of azimuth ambiguities, the synthesis of the sub-band and the CS imaging can realize 2-D high resolution and wide swath simultaneously. And the improved sub-band synthetic algorithm has more efficiency and practicality than the traditional sub-band synthetic algorithms in time frequency domain. The effectiveness of this method is verified with the theoretical analysis and the computer-based simulations.

Keywords: SAR MIMO High Resolution Wide Swath (HRWS) Doppler ambiguities Sub-band synthetic technology in frequency domain

Received 2010-10-08:

通讯作者: 陈倩 Email: chenqian19860123@sina.com

引用本文:

邓云凯, 陈倩, 祁海明, 郑慧芳, 刘亚东.一种基于频域子带合成的多发多收高分辨率SAR成像算法[J] 电子与信息学报, 2011, V33(5): 1082-1087

Deng Yun-Kai, Chen Qian, Qi Hai-Ming, Zheng Hui-Fang, Liu Ya-Dong. A High-resolution Imaging Algorithm for MIMO SAR Based on the Sub-band Synthesis in Frequency Domain[J], 2011, V33(5): 1082-1087

链接本文:

http://jeit.ie.ac.cn/CN/10.3724/SP.J.1146.2010.01067 或 http://jeit.ie.ac.cn/CN/Y2011/V33/I5/1082

Copyright 2010 by 电子与信息学报

Service

- ▶ 把本文推荐给朋友
- ▶ 加入我的书架
- ▶ 加入引用管理器
- ▶ Email Alert
- ▶ RSS

作者相关文章

- ▶ 邓云凯
- ▶ 陈倩
- ▶ 祁海明
- ▶ 郑慧芳
- ▶ 刘亚东