

基于样本学习的人像线条画生成系统

陈 洪, 郑南宁, 徐迎庆, 沈向洋

[Full-Text PDF](#) [Submission](#) [Back](#)

陈 洪¹, 郑南宁¹, 徐迎庆², 沈向洋² 1(西安交通大学 人工智能与机器人研究所, 陕西 西安 710049) 2(微软亚洲研究院, 北京 100080)

第一作者: 陈洪(1975—), 男, 浙江金华人, 博士, 主要研究领域为模式识别与智能系统, 机器视觉与图像处理.

联系人: 陈洪 Telephone: 86-10-62617711 ext 3146, E-mail: chennhong@yahoo.com

Received 2001-06-21; Accepted 2001-08-21

Abstract

In this paper, an example-based facial sketch system is presented, which automatically generates a sketch from an input image. All the example sketches are drawn with a particular style. There are two key elements in this system, a non-parametric sampling method and a flexible sketch model. Given an input image pixel and its neighborhood, the conditional distribution of a sketch point is computed by querying the examples and finding all similar neighborhoods. An expected sketch image is then drawn from the distribution to reflect the drawing style. Finally, good quality facial sketches are obtained.

Chen H, Zheng NN, Xu YQ, Shum HY. An example-based facial sketch generation system. *Journal of Software*, 2003, 14(2):202~208.

<http://www.jos.org.cn/1000-9825/14/202.htm>

摘要

介绍了一个基于样本学习的人像线条画生成系统. 该系统可以根据用户给定的正面人脸照片自动生成相应的人脸线条画. 在系统中有两个关键技术, 即非参数化采样方法和灵活的线条画模板. 对于给定图像上的任意像素点及其邻域, 通过在样本空间搜索并匹配所有的相似邻域, 计算该像素点在相应的线条画上出现的条件概率; 然后根据艺术家的风格和得到的条件概率绘制"期望的线条画"; 最后使用模板匹配得到最后的线条画. 此方法可以生成高质量的正面人脸线条画.

基金项目: Supported by the National Natural Science Foundation of China under Grant No.60024301 (国家自然科学基金)

References:

- [1] Rhodes G. Secrets of the face. *New Zealand Journal of Psychology*, 1994, 23(1):3~17.
- [2] Brennan SE. Caricature generator[MS. Thesis]. Cambridge, MA: MIT, 1982.
- [3] Tominaga M, Fukuoka S, Murakami K, Koshimizu H. Facial caricaturing with motion caricaturing in PICASSO system. In: Proceedings of the IEEE/ASME International Conference on Advanced Intelligent Mechatronics'97. 1997. 30~37.
- [4] Koshimizu H, Tominaga M, Fujiwara T, Murakami T. On KANSEI facial processing for computerized facial caricaturing system PICASSO. In: Proceedings of the IEEE International Conference on Systems, Man, and Cybernetics. 1999. 294~299.
- [5] <http://www.koshi-lab.sccs.chukyo-u.ac.jp/~fuji/pica2/>.
- [6] Li Y, Kobatake H. Extraction of facial sketch based on morphological processing. In: Proceedings of the 1997 IEEE International Conference on Image Processing. 1997. 316~319.

- [7] Nishino J, Kamyama T, Shira H, Odaka T, Ogura H. Linguistic knowledge acquisition system on facial caricature drawing system. In: Proceedings of the 1999 IEEE International Conference on Fuzzy Systems. 1999. 1591~1596.
- [8] Iwashita S, Takeda Y, Onisawa T. Expressive facial caricature drawing. In: Proceedings of the 1999 IEEE International Conference on Fuzzy Systems. 1999. 1597~1602.
- [9] Librande SE. Example-Based character drawing [MS. Thesis]. Cambridge, MA: MIT, 1992.
- [10] Poggio T, Girosi F. Networks for approximation and learning. In: Proceedings of the IEEE. 1990. 1481~1497.
- [11] Freeman WT, Tenenbaum JB, Pasztor E. An example-based approach to style translation for line drawings. MERL Technical Report, MERL-TR-99-11, Cambridge, MA, 1999.
- [12] Freeman WT, Pasztor E. Learning low-level vision. In: Proceedings of the 7th International Conference on Computer Vision. 1999. 1182~1189.
- [13] Efros AA, Leung TK. Texture synthesis by non-parametric sampling. In: Proceedings of the 7th International Conference on Computer Vision. 1999. 1033~1038.
- [14] Cootes TF, Taylor CJ. Statistical models of appearance for computer version. Technical Report, Manchester M13 9PT, University of Manchester, 2001.