

Volume 7

## Demulsification of Emulsion Liquid Membrane by Wetting Coalescence Materials

孙德智, 段晓东, 姜兆华, 周定

Department of Applied Chemistry, Ha' erbin Institute of Technology, Ha' erbin 150001, China

收稿日期 1998-1-26 修回日期 网络版发布日期 接受日期 1998-9-23

**摘要** Demulsification of emulsified water-in-oil droplets was worked out with the employment of wetting coalescence materials. Demulsification is carried out in conventional stirred-column and packed-column. Among the four kinds of natural fibers and two kinds of inorganic materials tested, natural fiber A, originated from wood shavings was found to give the best performance of demulsification. The demulsification efficiency can exceed 96.5% when demulsification conditions are optimized. The packed-column showed much better performance both in terms of demulsification efficiency and repeated use of the recovered oil phase for extracting cadmium in simulated wastewater. Operating variables governing the demulsification efficiency were investigated.

**关键词** [demulsification](#) [emulsion](#) [wet coalescence](#) [cadmium extraction](#)

分类号

**DOI:**

### Demulsification of Emulsion Liquid Membrane by Wetting Coalescence Materials

Sun Dezhi, Duan Xiaodong, Jiang Zhaohua, Zhou Ding

Department of Applied Chemistry, Ha' erbin Institute of Technology, Ha' erbin 150001, China

Received 1998-1-26 Revised Online Accepted 1998-9-23

**Abstract** Demulsification of emulsified water-in-oil droplets was worked out with the employment of wetting coalescence materials. Demulsification is carried out in conventional stirred-column and packed-column. Among the four kinds of natural fibers and two kinds of inorganic materials tested, natural fiber A, originated from wood shavings was found to give the best performance of demulsification. The demulsification efficiency can exceed 96.5% when demulsification conditions are optimized. The packed-column showed much better performance both in terms of demulsification efficiency and repeated use of the recovered oil phase for extracting cadmium in simulated wastewater. Operating variables governing the demulsification efficiency were investigated.

**Key words** [demulsification](#); [emulsion](#); [wet coalescence](#); [cadmium extraction](#)

通讯作者:

孙德智

作者个人主页: 孙德智; 段晓东; 姜兆华; 周定

扩展功能

本文信息

▶ [Supporting info](#)

▶ [PDF \(2329KB\)](#)

▶ [\[HTML全文\]\(0KB\)](#)

▶ [参考文献](#)

服务与反馈

▶ [把本文推荐给朋友](#)

▶ [加入我的书架](#)

▶ [加入引用管理器](#)

▶ [引用本文](#)

▶ [Email Alert](#)

▶ [文章反馈](#)

▶ [浏览反馈信息](#)

相关信息

▶ [本刊中包含“demulsification”的相关文章](#)

▶ 本文作者相关文章

- [孙德智](#)
- [段晓东](#)
- [姜兆华](#)
- [周定](#)