中国化学工程学报 2005 13 (5): 596-603 ISSN: 1004-9266 CN: 44-1063/R

SEPARATION SCIENCE & ENGINEERING

螺旋片导流式气液分离器的数值模拟与试验研究

周畅国[a],徐喜乐[a,b],凌祥[b]

[a] School of Mechanical Engineering, East China University of Science and Technology, Shanghai 200237, China

[b] College of Mechanical and Power Engineering, Nanjing University of Technology, Nanjing 210009, China

收稿日期 修回日期 网络版发布日期 接受日期

摘要 The gas/liquid spiral separator, a key component in the compressed air system, was used to remove liquid and oil from gas stream by centrifugal and gravitational forces. To optimize the design of the separator, the relationship between the performance and structural parameters of separators is studied. Computational fluid dynamics（CFD） method is employed to simulate the flow fields and calculate the pressure drop and separation efficiency of air-liquid spiral separators with different structural parameters. The RSM（Reynolds stress model）turbulence model is used to analyze the highly swirling flow fields while the stochastic trajectory model is used to simulate the traces of liquid droplets in the flow field. A simplified calculation formula of pressure drop in spiral structures is obtained by modifying Darcy’s equation and verified by experiment.

关键词 螺旋片导流式气液分离器 数值模拟 试验研究 压降 分离效率

分类号

DOI:

Numerical Simulation and Experimental Study on the Performance of Gas/liquid Spiral Separator

ZHOUGuoyan[a], TUShandong[a,b], LINGXiang[b]

[a] School of Mechanical Engineering, East China University of Science and Technology, Shanghai 200237, China

[b] College of Mechanical and Power Engineering, Nanjing University of Technology, Nanjing 210009, China

Received Revised Online Accepted

Abstract The gas/liquid spiral separator, a key component in the compressed air system, was used to remove liquid and oil from gas stream by centrifugal and gravitational forces. To optimize the design of the separator, the relationship between the performance and structural parameters of separators is studied. Computational fluid dynamics（CFD） method is employed to simulate the flow fields and calculate the pressure drop and separation efficiency of air-liquid spiral separators with different structural parameters. The RSM（Reynolds stress model）turbulence model is used to analyze the highly swirling flow fields while the stochastic trajectory model is used to simulate the traces of liquid droplets in the flow field. A simplified calculation formula of pressure drop in spiral structures is obtained by modifying Darcy’s equation and verified by experiment.

Key words gas/liquid separator; spiral structure; computational fluid dynamics; pressure drop; separation efficiency; numerical simulation

通讯作者：

周畅国 gyzhou88@163.com

作者个人主页：周畅国[a],徐喜乐[a,b],凌祥[b]

扩展功能

本文信息

Supporting info

PDF(2581KB)

[HTML全文](0KB)

参考文献

服务与反馈

把本文推荐给朋友

加入我的书架

加入引用管理器

引用本文

Email Alert

文章反馈

浏览反馈信息

相关信息

本刊中 包含“螺旋片导流式气液分离器”的 相关文章

本文作者相关文章

周畅国a

徐喜乐a

b

凌祥b