中国化学工程学报 2006 14 (5): 654-659 ISSN: 1004-9541 CN: 44-1641/TR

PROCESS AND PRODUCT TECHNOLOGY

废轮胎热解炭黑的表面修饰及其在平版印刷油墨中的应用

周治*[1], 王靖岱[1], 任晓红[1], 阳永荣[1], 蒋斌波[2]

[1] UNILAB Research Center for Chemical Reaction Engineering, Department of Chemical Engineering, Zhejiang University, Hangzhou 310027, China
[2] Department of Environmental Science and Engineering, Hangzhou Dianzi University, Hangzhou 310018, China

收稿日期 修回日期 网络版发布日期 接受日期

摘要 Pyrolysis has the potential of transforming waste into valuable products. Pyrolytic carbon black (PCB) is one of the most important products resulting from the pyrolysis of used tires. One of the most significant applications of modified pyrolytic carbon black is its use as pigment for offset printing ink to obtain high added values. Inverse gas chromatography (IGC) results show that a large quantity of inorganic matters and carbonaceous deposit are removed by treating the pyrolytic carbon black with nitric acid solution. Plenty of active sites originally occupied by inorganic ash and coke are recovered. The surface energy of pyrolytic carbon black (TWPC) modified by titanate-coupling agent-especially the specific interaction determined by the specific probe molecule, tolu-ene-shows the strong interaction between the TWPC and the synthetic resins. The offset printing ink performance confirms the IGC prediction. And TWPC has the great potential of applications in printing ink industry as pigment.

关键词 environmental engineering waste tires ink

分类号

Surface Modification of Pyrolytic Carbon Black from Waste Tires and Its Use as Pigment for Offset Printing Ink

ZHOU Zhi[a,b],WANG Jingdai[a],REN Xiaohong[a],YANG Yongrong[a], JIANG Binbo[b]

[a] UNILAB Research Center for Chemical Reaction Engineering, Department of Chemical Engineering, Zhejiang University, Hangzhou 310027, China
[b] Department of Environmental Science and Engineering, Hangzhou Dianzi University, Hangzhou 310018, China

Abstract

Pyrolysis has the potential of transforming waste into valuable products. Pyrolytic carbon black (PCB) is one of the most important products resulting from the pyrolysis of used tires. One of the most significant applications of modified pyrolytic carbon black is its use as pigment for offset printing ink to obtain high added values. Inverse gas chromatography (IGC) results show that a large quantity of inorganic matters and carbonaceous deposit are removed by treating the pyrolytic carbon black with nitric acid solution. Plenty of active sites originally occupied by inorganic ash and coke are recovered. The surface energy of pyrolytic carbon black (TWPC) modified by titanate-coupling agent-especially the specific interaction determined by the specific probe molecule, tolu-ene-shows the strong interaction between the TWPC and the synthetic resins. The offset printing ink performance confirms the IGC prediction. And TWPC has the great potential of applications in printing ink industry as pigment.

Key words environmental engineering waste tires ink

DOI:

扩展功能
本文信息
Supporting info
PDF(1210KB)
[HTML 0 条]
参考文献
服务与反馈
把该文章推荐给朋友
加入我的书架
加入引用管理器
复制索引
Email Alert
文章反馈
浏览反馈信息
相关信息
本刊中 包含“environmental engineering”的 相关文章
本文作者相关文章
周治
王
任晓红
阳永荣
蒋斌波