连续9年被评为"百种中国大土学术

首页 | 关于本刊 | 编 委 会 | 最新录用 | 过刊浏览 | 期刊征订 | 下载中心 | 广告服务 | 博客 | 论坛 | 联系我们 | English



论文













航空学报 » 1999, Vol. 20 » Issue (6):569-572 DOI:

最新目录 | 下期目录 | 过刊浏览 | 高级检索

<< Previous Articles | Next Articles >>

3-D C/SiC复合材料的氧化行为

殷小玮, 成来飞, 张立同, 徐永东

西北工业大学凝固技术国家重点实验室 陕西西安 710072

OXIDATION BEHAVIOR OF 3 D C/SiC COMPOSITES

YIN Xiao-wei, CHENG Lai-fei, ZHANG Li-tong, XU Yong-dong

State Key Laboratory of Solidification Technology, Northwestern Polytechnical University, Xi 'an 710072, China

Download: PDF (239KB) HTML OKB Export: BibTeX or EndNote (RIS) Supporting Info

摘要 研究了 3-D C / S i C 复合材料的氧化行为。在航空发动机燃气环境中的实验结果表明,C / S i C 复合材料的氧化失重与材料内部的大量孔隙以及涂层和基体中的微裂纹有关,其中基体内部的孔隙起着主要作用。在燃气中氧化后,C / S i C 复合材料力学性能的降低幅度比在干燥空气中的小,这是由于燃气中的氧分压较低。

关键词: 碳化硅 复合材料 燃气 氧化

Abstract: The oxidation properties of SiC sealed 3 D C/SiC composites were researched in this paper. The test results obtained in combustion environments showed that the weight losses of the composites were related to the pores and the microcracks in coating and matrix, where the pores produced a main effect on the results. The mechanical properties of C/SiC oxidized in combustion gas decreased less apparently than in dry air, which resulted from the low partial pressure of oxygen in the combustion atmosphere.

Keywords: silicon carbide compo sites combust ion gas oxidat ion

Received 1998-09-28; published 1999-12-25

Service

- ▶ 把本文推荐给朋友
- ▶ 加入我的书架
- ▶ 加入引用管理器
- ▶ Email Alert
- ▶ RSS

作者相关文章

- ▶ 殷小玮
- ▶成来飞
- ▶ 张立同
- 徐永东

引用本文:

殷小玮;成来飞;张立同;徐永东. 3-D C/SiC复合材料的氧化行为[J]. 航空学报, 1999, 20(6): 569-572.

YIN Xiao-wei; CHENG Lai-fei; ZHANG Li-tong; XU Yong-dong. OXIDATION BEHAVIOR OF 3 D C/SiC COMPOSITES[J]. Acta Aeronautica et Astronautica Sinica, 1999, 20(6): 569-572.

Copyright 2010 by 航空学报