



Engineering Village



航空学报 » 1998, Vol. 19 » Issue (2) : 116-119 DOI:

论文

[最新目录](#) | [下期目录](#) | [过刊浏览](#) | [高级检索](#)

[<< Previous Articles](#) | [Next Articles >>](#)

复杂目标高频区 RCS 的实时计算

于洋, 曾智勇, 朱劲松, 王宝发, 周荫清

北京航空航天大学电子工程系

COMPUTING HIGH FREQUENCY RCS OF COMPLEX TARGETS IN REAL TIME

Yu Yang, Zeng Zhiyong, Zhu Jinsong, Wang Baifa, Zhou Yingqing

Department of Electronic Engineering, Beijing University of Aeronautics and Astronautics, Beijing, 100083

摘要

参考文献

相关文章

Download: [PDF \(283KB\)](#) [HTML \(OKB\)](#) Export: BibTeX or EndNote (RIS) [Supporting Info](#)

摘要 提出一种在安装图形加速卡的高性能微机上实时计算复杂目标高频区雷达散射截面 (RCS) 的方法。该方法利用了“图形电磁计算 (G R E C O) ”的新技术。目标用 G 2 C a t m u l - o m (C-R) 几何样条模拟, 由图形加速卡硬件完成遮挡、消隐运算, 运用 P h o n g 照明模型着色渲染目标可见表面, 应用物理光学 (P O) 、等效电流法 (M E C) 、物理绕射理论 (P T D) 及阻抗边界条件 (I B C) 等方法计算目标高频区雷达散射截面 (RCS) 。

关键词:

Abstract: A new approach is presented to compute the high frequency radar cross section(RCS)of complex radar targets in real time, using a Personal Computer with a 3 D graphics hardware accelerator. This method implements a new technique called "Graphical Electromagnetic Computing(GRECO)".The target is modeled with G 2 Catmull Rom(C-R) geometric spline and the image of the target is rendered and displayed on the screen in real time using Phone illumination model and the 3 D graphics accelerator, and then the high frequency RCS can be computed through Physical Optics(PO),Method of Equivalent Currents(MEC),Physical Theory of Diffraction(PTD),and Impedance Boundary Condition (IBC) techniques.

Keywords:

Received 1997-09-01;

引用本文:

于洋;曾智勇;朱劲松;王宝发;周荫清. 复杂目标高频区 RCS 的实时计算[J]. 航空学报, 1998, 19(2): 116-119.

Yu Yang;Zeng Zhiyong;Zhu Jinsong;Wang Baifa;Zhou Yingqing . COMPUTING HIGH FREQUENCY RCS OF COMPLEX TARGETS IN REAL TIME[J]. Acta Aeronautica et Astronautica Sinica, 1998, 19(2): 116-119.

Service

- ▶ 把本文推荐给朋友
- ▶ 加入我的书架
- ▶ 加入引用管理器
- ▶ Email Alert
- ▶ RSS

作者相关文章